



MATERIAL SAFETY DATA SHEET

NOT A WORKPLACE HAZARDOUS SUBSTANCE ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA
MSDS ARRANGED IN ACCORDANCE WITH WORKSAFE NOHSC:2011 (1994)

| | |
|-----------|-------------------|
| Page: | 1 of 2 |
| Revision: | 5 |
| Date: | February 16, 2004 |
| Approved | |

COMPANY DETAILS

| | |
|-----------------------------|--|
| Company | Honeywell – Consumer Products Group Holt Lloyd Australasia Pty Limited |
| Address: | 5 Thomas Holt Drive North Ryde NSW 2113 |
| Telephone Number: | 61 2 9353 8152 |
| Fax Number | 61 2 9353 8150 |
| Email: | Holts-enquiry@honeywell.com |
| Emergency Telephone Number: | |

IDENTIFICATION

HOLTS AEROSOL ACRYLIC LACQUER

| | |
|--|---|
| Product Name: | Auto spray acrylic lacquer aerosol sprays, |
| Other Names: | Touch Up, Panel Spray, Wheel Paints, Fluoro Paints, Primers, Spraymatch, Spraymatch Clear and Primer, Metalcast |
| Manufacturer's Product Code: | DS*, PS* CSW*, CFL*, CPR*, HSM*, MC* |
| UN Number: | 1950 |
| Dangerous Goods Class & Subsidiary Risk: | 2.1 None allocated |
| Hazchem Code: | 2Y |
| Poisons Schedule Number: | None allocated |
| Use: | Aerosol paint |

PHYSICAL DESCRIPTION/PROPERTIES

| | |
|------------------------------|--|
| Appearance: | Aerosol, contents mobile liquid of characteristic colour |
| Boiling Point/Melting Point: | Not applicable |
| Vapour Pressure: | Internal pressure of aerosol can is 400-500 kPa @ 20C |
| Specific Gravity: | Liquid concentrate without propellant 0.80-1.00 @ 20C |
| Flashpoint: | Not applicable – contents in sealed container |
| Flammability Limits: | Of liquid contents without propellant – 2%-9.5% |
| Solubility in Water: | Immiscible |
| Other Properties: | None |

| INGREDIENTS | CAS NUMBER | PROPORTION % |
|------------------------------|------------|--------------|
| Acetone | 67-64-1 | <60% |
| Diacetone alcohol | 123-42-2 | <10% |
| Hydrocarbon propellant | 68514-31-8 | <30% |
| Aromatic hydrocarbons | | <10% |
| Acrylic polymer and pigments | | <10% |

All information contained in this document is as accurate as possible at the time of issue. The data contained herein is not an expressed or implied warranty or representation for which Holt Lloyd Australasia Pty Limited assumes legal responsibility.



HOLTS AEROSOL ACRYLIC LACQUER

| | |
|-----------|-------------------|
| Page: | 2 of 2 |
| Revision: | 5 |
| Date: | February 16, 2004 |
| Approved | |

HEALTH HAZARD INFORMATION**HEALTH EFFECTS****ACUTE**

Swallowed: May irritate mouth, throat and stomach. Also may cause vomiting, nausea and narcosis.

Eye: Severe irritant.

Skin: Has a defatting action on skin. May show redness or irritation.

Inhaled: May cause headaches and dizziness

CHRONIC:

Prolonged or continuous use may cause defatting of skin with subsequent cracking and dermatitis.

FIRST AID:

Swallowed: Do not induce vomiting. Seek medical attention.

Eye: Flush immediately with running water. If irritation occurs seek medical attention.

Skin: Wash with soap and water. Remove contaminated clothing. If irritation occurs, seek medical attention.

Inhaled: Move affected person to fresh air until symptoms subside. If symptoms persist, seek medical attention.

First Aid Facilities: No specific facilities required

Advice to Doctor: Treat symptomatically

PRECAUTIONS FOR USE

| | |
|-----------------------|--|
| Exposure Standards | 1450 mg/m ³ |
| Engineering Controls: | Use only in a well ventilated area |
| Personal Protection: | Not normally needed |
| Flammability | Highly flammable. Do not use close to any ignition source. |

SAFE HANDLING INFORMATION

Storage and Transport: Store out of reach of children and in a dry, cool place. Avoid direct sunlight. Class 2.1 Aerosol UN1950. Refer to Australian Code for Transport of Dangerous Goods.

Spills and Disposal: Cannot spill. If a can bursts, Mop up with adsorbent cloth then wash area with acetone or lacquer thinners (flammable).

Fire/Explosion Hazard: Flammable. May rocket or explode in fire. Fine water spray to cool containers: foam or powder extinguishers. Approach with caution if containers hot. Firefighters should wear protective clothing with self contained breathing apparatus.

| | |
|---------------------------|------|
| OTHER INFORMATION: | None |
|---------------------------|------|

All information contained in this document is as accurate as possible at the time of issue. The data contained herein is not an expressed or implied warranty or representation for which Holt Lloyd Australasia Pty Limited assumes legal responsibility.